## Merryman Modifications ENGINE REBUILD

CUSTOMER NAME:		
DATE 8 27/04 TYPE J SERIES Y	/EAR: D	ISCPLAC: 1275
BLOCK:		
Cooked Yes I No Line Bored Yes No Bored Yes I No		
Pistons CAJ3378-40 Size  1.5 Clearance  Make	Zi Replaced	☐ Reworked
Rings Gap Freeze Plugs	Replaced Page Replaced	<b>b.</b>
CRANKSHAFT:  Rod Big Size  Main Big Size  End Play  CIO  Twashers	☐ Replaced ☑ Replaced ☑ Replaced ☑ Replaced	Reworked
RODS: Bolts	☑ Replaced	<b>Reworked</b>
CAMSHAFT  Clearance: Int OIS H Exh OZO  Grind SPVP5-SN	Replaced	☐ Reworked
Brgs:	2 Replaced	
LIFTERS	El Replaced Compa	sit
OIL PUMP	W Replaced	☐ Reworked
PILOT BRG.	☐ Replaced	☐ Reworked
TIMING CHAIN	Replaced (24)	☐ Reworked
TENSIONER	☐ Replaced	☐ Reworked
HD GASKET SET	<b>M</b> Replaced	☐ Reworked
CONV SET	M Replaced	☐ Reworked
FRT SEAL REAR SEAL	M Replaced	☐ Reworked
PRESSURE RELIEF VALVE	☐ Replaced	☐ Reworked
	12 Replaced	☐ Reworked
PRESSURE RELIEF SPRING	E Replaced	☐ Reworked
FLYWHEEL	☑ Replaced	☐ Reworked
RING GEAR	Replaced	☐ Reworked
WATER PUMP	Car Replaced	□ Reworked
FAN BELT THE PROCEDULE	☐ Replaced	☐ Reworked
THERMOSTAT	Replaced Blance P.	
CLUTCH DISC	☐ Replaced	☐ Reworked
PRESSURE PLATE	<b>2</b> Replaced	☐ Reworked

TOP END:

Valve Job		R	Yes		No
Valve Springs			Yes	-	No
Adjusted Pressure		101	Yes	П	No
Guides Replaced		-	Yes	П	No
Guides Knurled			Yes	D	No
Stem Seals			Yes		No
Valves Replaced:			Yes	-	No
Int 4 Exh_ 4		_			140
Seats Replaced 4		M	Yes	П	No
Studs Replaced		1000			No
Head Magnifluxed	•		Yes	- 0	No
Head Degreased		, ,	Yes		No
Head Glassbeaded		,	Yes	П	No
Head CC'D 1633	i .		Yes		No
Ported			Yes		No
Compression B.5 - T.CC's	36.2	′			
Rocker Shaft		Ø	Yes .		No
Rocker Bushings			Yes - 1.5 Rockers		No
	Eq.				

MISC. PARTS:			Torque woil	Torquewa
Cam Part Number	VP7	Rod Bolts	55	38
Timing @ 0.020" Lift	25/51 66/26	HOAD STADS		40
Lobe Center Angle	106	HUA-D SIADS	60	40
Duration @ 0.020" In./Ex.	256 - 2772 2			
Cam Lobe Lift	0.286 - 0.293			
Lash Clearance (hot - max.)	15 In. / 15 Ex.			
Time To: (A.T.D.C.) #1 Inlet	103 - 104		<del></del>	
Best Rocker Ratio	1.26			•
Spring Seat Pressure	60		4	
Fully Open Pressure	155			·
Installed Height	1.365 - 1.375			-
Spring Part Number	VPS-02 -	· .	. 1	<u> </u>
Retainer Part Number	903-0000			
RPM Range	1500 - 6500			
Max. RPM	. 7000		,	
Idle Characteristics*.	Fairly Smooth -			
Suggested Comp. Ratio	8.5 - 9.5			
Adjustable Cam Gear	VCS-01			
Cam Duration @ 0.050" Lift	220/234			

# Alerryman Alodifications ENGINE REBUILD

CUSTOMER NAME:		
DATE: 3-18-05 TYPE: A Series	YEAR: 59	DISCPLAC: 998
BLOCK:		DIOCPLAC. 110
Bored Yes No Bored Yes No Pistons Approx /Zoove/Size	old tanked)  ONED to Clean  Replaced i  ONly	Oxloj)  □ Reworked
Rings OIO Gap  Freeze Plugs	☐ Replaced☐ Replaced	
CRANKSHAFT:  Rod Big Size Stb  Main Big Size Stb  End Play Sto Twashers	☐ Replaced ☐ Replaced ☑ Replaced ☐ Replaced	☐ Reworked
RODS:		
Bolts	☐ Replaced	☐ Reworked
CAMSHAFT Clearance: Int 6/6 Exh 6/8 Grind SPVP4	Replaced	☐ Reworked
Brgs:	☐ Replaced	
LIFTERS OIL PUMP PILOT BRG. TIMING CHAIN TENSIONER HD GASKET SET CONV SET FRT SEAL REAR SEAL PRESSURE RELIEF VALVE PRESSURE RELIEF SPRING FLYWHEEL RING GEAR WATER PUMP FAN BELT THERMOSTAT CLUTCH DISC PRESSURE PLATE	☐ Replaced	☐ Reworked

TOP END:		
Valve Job	☑ Yes	□ No
Valve Springs Adjusted Pressure	□ Yes	□ No
Guides Replaced	☐ Yes ☐ Yes	☑ No ☑ No
Guides Knurled	□ Yes	☑ No
Stem Seals	□ Yes	☑ No
Valves Replaced:  Int Exh	□ Yes	M No
Seats Replaced	☐ Yes	⊠ No
Studs Replaced	□ Yes	☑ No
Head Magnifluxed Head Degreased	☑ Yes	□ No
Head Glassbeaded	☑ Yes □ Yes	□ No ☑ No
Head CC'D Prev Done	□ Yes	⊠ No
Ported	□ Yes	☑ No
Rocker Shaft	☐ Yes	F No.
Rocker Bushings	☐ Yes	Ø No ☑ No
MISC. PARTS:		
Notes. END Place -002	The second secon	
Main Bug Cl OOZ		
Rod Big U OOZ		
Rod Torque 37416	(shetch occ	05006)
Lobe Center Angle	(shelel .00 102-5 #	1 1xtake
<b>V</b>		
ADD. Note: - Small Crack S FACE from rwater Jacket #2 push Ross Hole. (o.	tacking ix Cylin	ndew Henris Cousket
FACE from runter Jacket	heading too	war
to out Do the la	6 Co 11	
The Just Nois Me. (0)	KTOL NOW)	
	*	


# WINPEP

59 SPEEDWELL GT

TUNING RUNS 3RD GEAR

Max Power = 91.21 Max Torque = 130.62

#### DYNOJET Performance Evaluation Program



## Merryman Modifications ENGINE REBUILD

DATE 2008 TYPE ALL YEAR: DISCPLAC: /2 75  BLOCK:  Cooked Yes No Bored Yes No Pistons Of Clearance Nake Rings Freeze Plugs Replaced Replaced Reworked Replaced End Play DO3 Twashers Replaced Rep	CUSTOMER NAME:		
Cooked   Yes   No   No   Bored   Yes   No   No   Size   Clearance   Clearance   Make   Replaced   Reworked   Replaced   Reworked   Replaced   Replaced   Reworked   Replaced   Reworked   Replaced   Replaced   Reworked   Replaced   Replaced   Reworked   R	DATE: 2008 TYPE: Sprike	YEAR:	DISCPLAC: 1275
Replaced   Reworked   Replaced   Reworked   Replaced   Reworked   Replaced   Reworked   Reworked   Replaced	Cooked	☐ Replaced	□ Reworked Ca j 3378. 40
Bolts   Replaced   Reworked   Reworked   Reworked   Reworked   Replaced   Reworked   Reworked   Reworked   Replaced   Reworked   Reworked   Reworked   Replaced   Reworked   Rew	CRANKSHAFT:  Rod Big Size 010 0015 - 015 -	Replaced Replaced Replaced	□ Reworked
Replaced   Reworked   Reworked   Replaced   Reworked	Bolts	☐ Replaced	☐ Reworked
OIL PUMP  PILOT BRG.  Replaced  Reworked  Reworked  Replaced  Reworked  Reworked  Replaced  Reworked  Reworked  Replaced  Reworked  Reworked  Replaced  Reworked  Reworked  Replaced  Reworked  Reworked	Grind Linchangeel	19 2 CONTROL CONTROL	☐ Reworked
CLUTCH DISC   Replaced  Reworked  Reworked	OIL PUMP PILOT BRG. TIMING CHAIN TENSIONER HD GASKET SET CONV SET FRT SEAL REAR SEAL PRESSURE RELIEF VALVE PRESSURE RELIEF SPRING FLYWHEEL RING GEAR WATER PUMP FAN BELT THERMOSTAT	□ Replaced	☐ Reworked

TOP END:			
Valve Springs		☑ Yes	D No
Valve Springs Adjusted Pressure		□ Yes	△ No
Guides Replaced		☐ Yes	□ No
Guides Knurled		□ Yes	□ No
Stem Seals		□ Yes	□ No
Valves Replaced:		□ Yes	□ No
Int	Exh		
Seats Replaced	and the second s	□ Yes	□ No
Studs Replaced		□ Yes	□ No
Head Magnifluxed Head Degreased		Yes Yes	□ No
Head Glassbeaded		⊠ Yes	□ No
Head CC'D	Annual Control	☐ Yes	□ No
Ported		□ Yes	□ No
Rocker Shaft		□ Yes	□ No
Rocker Bushings		□ Yes	□ No
MISC. PARTS:			
Profito La Para		- F	Filtress and
	Y SANSA	The transfer of the same of	
*			
			28-20 1890 Ave. See
La Participa de la Caracteria de la Cara			
		Market and the second s	
Server a responsible			
to destruct the second		y	
(6.20085.) 1			
	*		
	1000		

### Merryman Modifications ENGINE REBUILD

CUSTOMER NAME:	<u> </u>
DATE: 12 2011 TYPE: Spile YEAR	DISCPLAC:/275
BLOCK:  Cooked Ves No Line Bored Yes No Bored Yes No Pistons 305/46 Size Old Rep  John A Chie TE Make Rings 20674 Old Gap Freeze Plugs	placed
	☐ Replaced ☐ Reworked  placed  placed  Replaced
RODS: ARP Bolts Tourque 38 A. Ubs collabor	☐ Reworked ☐ Replaced
CAMSHAFT  Clearance: Int O18 Exh 020  Grind wichanged  Brgs:	☐ Replaced ☐ Reworked ☐ Replaced
LIFTERS OIL PUMP PILOT BRG. TIMING CHAIN TENSIONER HD GASKET SET CONV SET FRT SEAL REAR SEAL PRESSURE RELIEF VALVE PRESSURE RELIEF SPRING FLYWHEEL RING GEAR WATER PUMP FAN BELT THERMOSTAT CLUTCH DISC	□ Replaced         □ Reworked           □ Reworked         □ Reworked           □ Replaced         □ Reworked           □ Replaced         □ Reworked           □ Replaced         □ Reworked           □ Replaced         □ Reworked           <

Valve Job Valve Springs Adjusted Pressure Guides Replaced Guides Knurled Stem Seals Valves Replaced: Int Seats Replaced Studs Replaced Head Magnifluxed Head Degreased Head Glassbeaded Head CC'D Ported  Rocker Shaft Rocker Bushings	✓ Yes  ✓ Yes	No N	
MISC. PARTS:  Replacement Like	s from V	J.P.	